


Features:

- IP65 Outdoor Rated
- powerCON TRUE1 Power In/Out
- Motorized Zoom (5 to 45-degrees)
- WiFLY EXR wireless DMX



Photometric

Photometric							
45° (LUX)	R	1436	468	221	138	90	
	G	4304	1316	582	360	242	
	В	1121	351	157	100	70	(LUX)
	W	5107	1532	698	423	284	
	RGBW	9124	2785	1271	751	500	
	_						-
5° (LUX)	R	8025	4113	2186	1265	885	
	G	21050	11650	6469	3916	2467	1
	В	5710	3113	1632	983	608	(LUX)
	W	28070	12840	6671	3995	2693	1
	DCDM	40220	24000	12000	7000	EEDE	1



Technical Information:

Optical

- Light Source: 7 x 15 Watt Quad (RGBW) LEDs
- LED Life Expectancy: 50,000 Hrs
- Beam Angle: (5 to 45-degrees)

Technical Features

- Compatible with ADJ's WiFLY Protocol
- Strobe (electronic)
- 64 built-in Color Macros
- 5 Operational Modes: Color Change Mode; Color Fade Mode; Auto (Program Run) Mode; Sound Active Mode and DMX-512 Mode
- 4-button LED Display on rear panel
- Electronic Dimming 0 100%
- Flicker Free
- WiFLY EXR DMX Range: 2,500 feet /700M (line of site)
- Wifly On/Off
- Dual bracket yoke allows fixture to be hung or set on the ground

Connections

- Power Input: powerCON True1 AC
- Power Pass through: powerCON True1
- Data: 3 Seatronic IP connection

Control

- 12 DMX Channel Modes
- 16 Selectable WiFLY Address Channels

Electrical

- Input Voltage: 100-240V 50Hz/60Hz (Auto Sensing)
- Power draw 120V 60Hz: 128W
- Power draw 220V 50Hz: 128W

Physical

- Dimensions (LxWxH): 10.5" x 13.75" x 15" / 270 x 350 x 380mm
- Weight: 25 lbs / 11 kg.
- Metal Black Housing
- IP 65

Whats Included

- powerCON True1 Edison Cable (1M)
- Manual











©2017 ADJ Products, LLC www.adj.com

