



## NET 8

ADJ's NET 8 is a versatile 4-port DMX over Ethernet node that can be mounted in a 19-inch rack case. It is compatible with DMX-512, RDM, Artnet and sACN protocols, ensuring a broad spectrum of integration possibilities. The 1.7-inch LED display facilitates easy configuration, allowing you to fine-tune settings and monitor status at a glance.

NET 8, a cutting-edge 8-port DMX over Ethernet node that revolutionizes your lighting control experience. This versatile node supports ArtNet, sACN, DMX and RDM protocols, providing a seamless integration platform for your dynamic lighting setups. Whether you prefer traditional Line Voltage or the convenience of Power over Ethernet (PoE), NET 8 empowers you with flexible power options to suit diverse installation scenarios.

Configuring NET 8 is a breeze, offering the choice between DHCP or Static IP Address settings. This adaptability ensures that the node seamlessly integrates into your existing network infrastructure. What sets NET 8 apart is its user-friendly interface, allowing configuration adjustments from the unit menu or the convenience of a web browser. Whether you're on-site or managing your lighting system remotely, NET 8 puts control at your fingertips. NET 8 is a one space, 19-inch rack mountable node that helps you expand from one DMX universe to eight (when used with an ArtNet compatible lighting controller).





## FEATURES:

- ArtNet / sACN /DMX, 8-Port Node
- Line Voltage or Power over Ethernet (PoE) powered
- DHCP or Static IP Address
- 1.7" LCD Display
- Configurable from unit menu or web browser

## PROTOCOLS:

- DMX512
- RDM
- Artnet
- sACN

## PHYSICAL:

- 2x Indoor RJ45 Input & Output
- 8x 5-pin XLR Input / Output

## DIMENSIONS / WEIGHT:

- Length: 5.09" (129.3mm)
- Width: 19" (482.5mm)
- Height: 1.73" (43.8mm)
- Weight: 4.76lbs. (2.16kg)

## POWER:

- AC Input 95-240V,50/60Hz
- PoE 802.3af
- AC Power: 15W
- PoE Power: 15W
- Power Consumption: 5.7W @ 120V and 5.9W @ 230V
- Power Input Protection: Fuse, T1.25A/250V (5.2x20mm)

## THERMAL:

- Ambient Operational Temperature: -4°F to 113°F (-20°C to 45°C)
- Humidity: <75%
- Storage Temperature: 77°F (25°C)

## APPROVALS / RATINGS:

- CE
- cETLus (Pending)
- FCC
- IP20

## WHAT'S INCLUDED:

- Indoor Locking Power Cord