

Stryker Beam

Light Efficiency:

7 Lumen/Watt

Light Quality:

CRI: 77.4

Color Temperature:

8908 K

Output: 1017 lm

Peak: 22854 cd


Power: 144.8 W

PF: 0.65



Beam Angle

11.3°




Test:

Frost

Date:

7/5/2023

Note:




CIE 1931

x: 0.292


y: 0.287

Spectra

Dominant Wavelength: 450nm





Power




Voltage: 116 V
Current: 1.93 A
Frequency: 60 Hz


Color Details



TM30: 73.1



CRI: 77.4 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
79.8	79.4	72.6	81.6	78.8	68.6	84.0	74.8	12.1	44.9	78.8	45.2	79.1	84.1	80.2


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
72.2	72.0	65.1	69.4	75.9	88.5	91.2	77.5	70.6	58.2	40.3	70.6	78.8	80.5	75.3	84.1

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
87.9	91.9	60.8	47.7	62.7	72.6	83.4	91.0	83.3	68.2	59.7	62.3	68.5	67.8	77.1


CQS: 69.6



Color Parameters

Color Temperature	Color Rendering Index	Red Component	Color Fidelity	Color Gamut	Color Quality Scale	Color Coordinate CIE 1931	Color Coordinate CIE 1931	Color Coordinate	Color Coordinate	Color Deviation from Black Body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
8908 K	77.4	12.1	73.1	95.4	69.6	0.292	0.287	0.199	0.294	-0.0106

Beam Details



Beam Intensities from 1-20m

m	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
ft	3.3	6.6	9.8	13.1	16.4	19.7	23	26.2	29.5	32.8	36.1	39.4	42.7	45.9	49.2	52.5	55.8	59.1	62.3	65.6
lx	22821	5705	2536	1426	913	634	466	357	282	228	189	158	135	116	101	89	79	70	63	57
fcd	2120.2	530	235.6	132.5	84.8	58.9	43.3	33.1	26.2	21.2	17.5	14.7	12.5	10.8	9.4	8.3	7.3	6.5	5.9	5.3

Intensities in 0° C-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
22.8K	22.3K	20.9K	18.9K	16.2K	13.3K	10.4K	7.8K	5.6K	3.9K	2.6K	1.7K	1.1K	0.7K	0.4K	0.2K	0.1K	0.0K	0.0K	0.0K
100%	98%	92%	83%	71%	58%	45%	34%	24%	17%	11%	7%	5%	3%	2%	1%	0%	0%	0%	0%

Intensities in 90° C-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
22.8K	22.3K	20.9K	18.9K	16.2K	13.3K	10.4K	7.8K	5.6K	3.9K	2.6K	1.7K	1.1K	0.7K	0.4K	0.2K	0.1K	0.0K	0.0K	0.0K
100%	98%	92%	83%	71%	58%	45%	34%	24%	17%	11%	7%	5%	3%	2%	1%	0%	0%	0%	0%

Intensities in 180° C-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
22.8K	22.5K	21.2K	19.0K	16.2K	13.3K	10.4K	7.9K	5.7K	4.0K	2.7K	1.8K	1.1K	0.7K	0.4K	0.3K	0.1K	0.1K	0.0K	0.0K
100%	99%	93%	83%	71%	58%	46%	35%	25%	17%	12%	8%	5%	3%	2%	1%	1%	0%	0%	0%

Intensities in 270° C-plane

0°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	13°	14°	15°	16°	17°	18°	19°
22.8K	22.5K	21.2K	19.0K	16.2K	13.3K	10.4K	7.9K	5.7K	4.0K	2.7K	1.8K	1.1K	0.7K	0.4K	0.3K	0.1K	0.1K	0.0K	0.0K
100%	99%	93%	83%	71%	58%	46%	35%	25%	17%	12%	8%	5%	3%	2%	1%	1%	0%	0%	0%

Beam Angle 50%	Field Angle 10%	Cutoff Angle 2,5%	Intensity Ratio in 120° Cone	Intensity Ratio in 90° Cone
11.3°	20.6°	26.7°	100.0%	100.0%